

DS41-1000

- Type 2 AC surge protector
- In : 20 kA
- Imax : 40 kA
- Pluggable module for each phase
- Remote signaling option
- NF EN 61643-11, CEI 61643-11 compliance
- UL1449 ed.4

Electrical Characteristics		
SPD type *following IEC test*		2
Network		1000 Vac
Nominal line voltage	*Un*	1000 Vac
Max. AC operating voltage L-N	*Uc*	1100 Vac
Temporary Over Voltage (TOV) Charasteristics - 5 sec. *without disconnection*	*UT*	1400 Vac withstand
Temporary Over Voltage (TOV) Charasteristics - 120 mn *without disconnection or with safety disconnection*	*UT*	1840 Vac disconnection
Residual Current *Leakage current to Ground*	*Ipe*	< 0.5 mA
Operating current *Continious current at Uc*	*Ic*	0.5 mA
Follow current	*If*	None
Nominal discharge current *15 x 8/20 µs impulses*	*In*	20 kA
Max. discharge current *max. withstand @ 8/20 µs by pole*	*Imax*	40 kA
Admissible short-circuit current	*Isccr*	25000 A
Connection mode(s)		L/PE
Protection mode(s)		Common mode
Protection level *@ In (8/20µs)*	*Up*	5 kV

Mechanical Characteristics		
Technology		MOV
SPD configuration		1-pole
Connection to Network		By screw terminals: 2.5-25 mm² / by bus
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN60715)
Housing material		Thermoplastic UL94-V0
Operating temperature		-40/+85°C
Protection rating		IP20
Failsafe behavior		Disconnection
Disconnection indicator		1 mechanical indicator
Spare module(s)		DSM40-1000
Remote signaling of disconnection		option DS41S-1000 : output on changeover contact
Dimensions		See diagram

Disconnectors		
Thermal disconnector		Internal
Installation ground fault breaker		Type 'S' or delayed
Fuses		Fuses type gG - 50 A

V: High-energy varistor
Ft: Thermal fuse
t°: Thermal disconnection system
MI: Disconnection indicator

Standards		
Standards compliance		IEC 61643-11 / EN 61643-11
Certification		EAC
Part Number		462901